

The below references should be used as guidance only

LOXEAL	LOCTITE	LOXEAL	LOCTITE
32-18	221	15-45	545
24-18	222	85-55	554
24-18	222MS	18-65	565
26-18	225	53-14	566
52-03	241	18-10	567
54-03	242	18-10	572
55-03	243	28-10	573
56-03	245	58-14	574
32-18	259	15-36	576
55-04	262	58-11	577
83-54	270	56-14	582
83-55	271	86-55	586
86-72	272	70-13	589
83-55	273	18-65 / 18-10	592
52-03	274	59-20 N	598
86-54	275	82-21	601
86-53	277	82-33	603
70-14	290	86-86	620
33-47A	326	85-21	638
33-22 A+B	327 A+B	83-31	640
33-00	330	53-11	641
UV 30-22	350	83-21	648
UV 30-20	358	85-02	648 A.V.
IST 29	380	82-01	648 B.V.
IST 43	401	89-51	660
IST 25	405	52-11	672
IST 32	406	82-13	675
IST 41	4062	83-80	680
IST 54	407	ATT. 20	737
IST 47	409	CR1 REMOVER	768
IST 34	414	ATT. 7	770
IST 17	415	ATT. 18	7090
IST 27	416	ATT. 9	7452
IST 20	420	ATT. 11	7471
IST 43T	424	ATT. 11	7649
IST 45	431	70-14	A
IST 47	454	70-13	AA
IST 63	460	82-13	AAV
IST 29	480	83-54	AV
IST 10	493	83-54	AVV
IST 23	495	86-55	AVX
IST 14	496	52-11	B
IST 54	498	52-03	C
56-03	509	54-03	CV
59-10	510	56-14	CVX
58-10	511	32-18	E
58-15	515	24-18	EV
58-31	518	12-36	H
53-14	542	15-36	HVX

The cross reference is exclusively based on the results obtained by practical tests on specific applications and on our present state of acknowledge and experience. The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. Loxeal is a trademark of Loxeal Srl